

OXYGEN THERAPY

Medical Gas Regulators

Solutions for Life

286MB Series Brass Medical Gas Regulators



286MB-15LY2
Click-Style Regulator with Hose Barb Outlet,
two DISS Outlets and CGA 870 Yoke Inlet



286MB-15LBS1-FBS
Click-Style Regulator with hose barb outlet,
BS 5682 coupler outlet and BS 3 inlet

Features

- Available in Oxygen
- Chrome-plated brass body
- 3000 psi maximum inlet pressure
- 1-1/2" diameter UL-listed gauge
- Complies to CGA standards
- Internal relief valve
- Hose barb outlet
- Piston design regulator
- Sintered bronze inlet filter for longer service life
- Easy to read flow rate window
- Meets ignition testing for oxygen service
- Pre-set: 50 psi, options: 58 or 65 psi

Flow Rate

Flow Settings	Flow Rate (LPM)
4L	0, 0.25, 0.5, 0.75, 1, 1.25, 1.5, 2, 2.5, 3, 3.5, 4
8L	0, 0.5, 1, 1.5, 2, 2.5, 3, 4, 5, 6, 7, 8
15L	0, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 12, 15
25L	0, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 15, 25

Ordering Information

Ex:	130M	- 4L	Y	2	- FBS
	Series	Flow Settings (LPM)	Inlet Connector	DISS Outlet (s)	Coupler Outlet (s)
	130M	4L	None: CGA540	None: without DISS Outlet	None: without coupler
	284MA	8L	Y: CGA870	1: with one DISS outlet	FOH: Ohmeda® coupler
	285MA	15L	BS: BP-BS341-3	2: with two DISS outlets	FDS: DISS hex coupler
	286MB	25L	BSh: BP-BS341-3H	D: DISS outlet replacing hose barb	FDH: DISS handwheel coupler
	287MA	2CK: None, Pre-set: 50 psi		FFS: French (NF S 90-116) coupler
	288MA				FGS: German (DIN 13260-2) coupler
					FBS: British (BS5682-1998) coupler
					FJIS: Japanese style coupler
					FSIS: Australian (AS2896) coupler